



China 6204 Bearing Supplier



6201 Bearing 2D drawings and 3D CAD models

NSK/Koyo/NTN/Fak/NACHI Distributor
Supply Deep Groove Bearing 6201 6203 6205 6207
6209 6211 for Auto Parts/Agricultural
Machinery/Spare Parts

Bearing No. 6201

| | |
|-------------------------------|--------------------------|
| Size | 12x32x10 mm |
| Bore Diameter | 12 mm |
| Outer Diameter | 32 mm |
| Width | 10 mm |
| d | 12 mm |
| D | 32 mm |
| B | 10 mm |
| C | 10 mm |
| r min. | 0.6 mm |
| da min. | 17 mm |
| Da max. | 27 mm |
| ra max. | 0.6 mm |
| Weight | 0.037 Kg |
| Basic dynamic load rating (C) | 6,8 kN |
| Basic static load rating (C0) | 3,05 kN |
| (Grease) Lubrication Speed | 22000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |



China 6204 Bearing Supplier

| | |
|---------------------------------|---|
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 12MM Bore; 32MM Outside Diameter; 10MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Weight / LBS | 0.081 |
| Bore | 0.472 Inch 12 Millimeter |
| Outside Diameter | 1.26 Inch 32 Millimeter |
| Outer Race Width | 0.394 Inch 10 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 12 mm |
| Width | 10 mm |
| | |



China 6204 Bearing Supplier

| | |
|-------------------------|-------------------|
| Fillet Radius/Chamfer | 0.6 mm |
| Dynamic Load Rating | 6,800 N |
| Static Load Rating | 3,050 N |
| Limiting Speed - Grease | 22,000 rpm |
| Limiting Speed - Oil | 28,000 rpm |
| Factor fo | 12.3 |
| Radial Clearance | 0.003 to 0.018 mm |
| da (min) | 17 mm |
| Da (max) | 27 mm |
| ra (max) | 0.6 mm |