



China 6204 Bearing Supplier



Industrial Bearing SKF Rolamento SKF Rulman Bilya 607-2rsh 608-2z C3 609 2RS/Zz SKF Ball Bearing

Bearing No. 607-2rsh

607-2rsh Bearing 2D drawings and 3D CAD models

Size	7x19x6 mm
Bore Diameter	7 mm
Outer Diameter	19 mm
Width	6 mm
d	7 mm
D	19 mm
B	6 mm
C	6 mm
d1	– mm
d2	9,5 mm
r1 min.	9 mm
r2 min.	9 mm
D1	16,5 mm
D2	0,3 mm
da min.	9,4 mm
Da max.	17 mm
ra max.	0,3 mm
Weight	0,0078 Kg
Basic dynamic load rating (C)	2,34 kN
Basic static load rating (C0)	0,95 kN
Fatigue load limit (Pu)	0,04
Reference speed	– r/min
Limiting speed	19000 r/min
Calculation factor (f0)	13



China 6204 Bearing Supplier

Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	7316571839219
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	7MM Bore; 19MM Outside Diameter; 6MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; Co
Other Features	Deep Groove NBR Seal
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	607-2RSH
Weight / LBS	0.022



China 6204 Bearing Supplier

Outer Race Width	0.236 Inch 6 Millimeter
Bore	0.276 Inch 7 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	0.748 Inch 19 Millimeter
bore diameter:	7 mm
static load capacity:	0.95 kN
outside diameter:	19 mm
precision rating:	ABEC 3 (ISO Class 6)
overall width:	6 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
outer ring width:	6 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
internal clearance:	C0
maximum rpm:	24000 RPM
operating temperature range:	-40 to +210 ° F
series:	60
dynamic load capacity:	2.34 kN
d_2	9.5 mm
D_2	16.5 mm
d_a min.	9 mm
d_a max.	9.4 mm
D_a max.	17 mm
r_a max.	0.3 mm
Basic dynamic load rating C	2.34 kN
Basic static load rating C_0	0.95 kN
Fatigue load limit P_u	0.04 kN
Calculation factor k_r	0.025



China 6204 Bearing Supplier

Calculation factor f_0	13
Mass bearing	0.0078 kg